


THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY.

	REVISIONS			
REV.	DESCRIPTION	ECO	DATE	APPROVED
В	ADD ISOMETRIC VIEW	18-010	11/14/18	P.T





Ø14.8 [Ø.58]

3X PIN Ø1.0 [.04]

ON THE CIRCLE
Ø12.4 [Ø.49]
@120° APART

R1.0 [R.04]

SEATING PLANE
(SOLDER SIDE)

3X R2.0 [R.08]

3X 2.5 [.10]-3.0 [.12]



Terminal:

Port (1)-(2): Input-Output

SEATING PLANE

Port (2)-(3) Port (3)-(1)

Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	3400		3600
Insertion Loss (dB)		< .25	.30
Isolation (dB)	20	> 22	
Return Loss (dB)	20	> 22	

Notes:

1. Typical Values Represent Performance @ +23 °C

3X Ø1.00 [.039]

PIN

S-Parameters to be measured by connecting Port 1 and 2 to VNA, and Port 3 to Load with return loss 30dB or higher

Power & Temperature Ratings


Parameter	Maximum
Forward PWR Peak/AVG	500/30 Watts
Reverse Power CW	30 Watts
Operating Temperature	-40 to +85° C
Storage Temperature	-50 to +125° C

Permanent damage to the Device or reduce reliability if exceeding any of the limits.

Fort (1),(2)and (3): DC connected and floating as the only ground connection

Finish:

- 1. Housing: Silver plated
- 2. Pin: Gold plated
- 3. Coplanarity specification: 0.10 [.004] MAX.



CW SMD CIRCULATOR MODEL: RFCR5827

