

Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	3600		4200
Insertion Loss: In-Out (dB)		< 0.35	0.40
Isolation: Out-In (dB)	18	> 20	
Return Loss (dB)	18	> 20	

Port (1)-(2): Input-Output

Port (2)-(3)

Port (3)-(1)

Notes:

- 1. Typical Values Represent Performance @ +23 °C.
- 2. S-Parameters to be measured by connecting Port 1 and 2 to VNA, and Port 3 to Load with return loss 30dB or higher

Power & Temperature Ratings


Parameter	Maximum
Forward PWR Peak/AVG	500/30 Watts
Reverse Power CW	30 Watts
Operating Temperature	-40 to +85° C
Storage Temperature	-50 to +125° C

Permanent damage to the Device or reduce reliability if exceeding any

Port (1),(2)and (3): DC connected and floating as the only ground connection.

Finish:

- 1. Housing: Silver plated
- 2. Pin: Gold plated
- 3. Coplanarity specification: 0.10 [.004] MAX.



CW SMD CIRCULATOR MODEL: RFCR5842D

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS (INCHES): TOLERANCES ARE:	THIRD ANGLE PROJECTION		DECL (A)					
1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° SURFACE ROUGHNESS 16	APPROVALS	DATE						
REMOVE ALL BURRS AND BREAK SHARP EDGES.	DRAWN BY:							
SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5	CHECKED BY:		TITLE					
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RE	DESIGN BY:		OUTLINE/SPECS					
CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR	ENGINEER BY:		T OUTLINE/SPECS					
INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO	MFG. ENGR.		SIZE CAGE NO. DWG NO. REV.		IREV.			
DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE	Q.A.		Α	CAGE NO.		400	00	B
AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL." PROG. MGMT/MKT			A		CR5842D-OS		-08	
DO NOT SCALE DRAWING		_	SCALE	E: FULL			SHEET 1 OF 1	