


THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY. DO NOT REVISE MANUALLY.

REVISIONS

REV.	DESCRIPTION	ECO	DATE	APPROVED
1	INITIAL RELEASE	I.R.	03/06/14	P.T



Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (GHz)	8.0		18.0
Insertion Loss (dB)		< .70	.90
Isolation (dB)	15	> 16	
Return Loss (dB)	15	> 16	

Power & Temperature Ratings

Parameter	Maximum
Forward PWR Peak/AVG	250/25 Watts
Reverse Power CW	10 Watts
Operating Temperature	-40 to +85° C
Storage Temperature	-40 to +95° C

Notes:

- Typical Values Represent Mid-Band Performance @ +23 °C.
- Tab dimensions: .62[0.24]Width x 2.0[0.08]Length x .20[0.008]Thick

CW OCTAVE CIRCULATOR MODEL: RFCR8934

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]: TOLERANCES ARE: 1 PLACE DECIMAL ±.2 [±.01] ANGULAR: ±1.0° 2 PLACE DECIMAL ±.10 [±.004] SURFACE ROUGHNESS 16/		THIRD ANGLE PROJECTION 		RFCI			
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5		APPROVALS		DATE		TITLE	
PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RF CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."		DRAWN BY:				OUTLINE/SPECS	
		CHECKED BY:				SIZE	
		DESIGN BY:				CAGE NO.	
		ENGINEER BY:				DWG NO.	
		MFG. ENGR.				CR8934-OS	
		Q.A.				REV.	
		PROG. MGMT/MKT				1	
DO NOT SCALE DRAWING				SCALE: FULL		SHEET 1 OF 1	