



RoHS

	29.0 [1.14]-	_
	26.5 [1.04]	
2X 5.1 [.20] 2	RFCI RFSL5311	(Ø28.4 [Ø1.12])
[.75]		Ø25.4
<u> † </u>		[Ø1.00]
11.0	0 [.43]	TERMINATION





SolderMask Pattern

Recommended Footprint Copper-SolderMask Pattern

The Land Pattern should be with good thermal conductivity

Finish:

- 1. Housing: Silver plated
- 2. Pin: Gold plated
- 3. Coplanarity specification: 0.10 [.004] MAX.

Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	1200		1400
Insertion Loss (dB)		< .25	.35
Isolation (dB)	20	> 23	
Return Loss (dB)	22	> 23	

Power & Temperature Ratings

Parameter	Maximum	
Forward PWR Peak/AVG	500/100 Watts	
Reverse Power CW	80 Watts	
Termination Rating (See Note 2)	100 Watts	
Operating Temperature	-40 to +85° C	
Storage Temperature	-50 to +125° C	

NOTES:

- 1. Typical Values Represent Performance @ +23 °C.
- 2. Isolator Flange held to +85°C; 30 Min. maximum Duration.

CW SMD ISOLATOR MODEL: RFSL5311

