

DWG. NO. SL5405-OS SHT REV


THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY. DO NOT REVISE MANUALLY.

	REVISIONS						
REV.	DESCRIPTION	ECO	DATE	APPROVED			
В	ADD ISOMETRIC VIEW	18-010	11/14/18	P.T			











Port (1): Input Port (2): Output



## <u>Finish:</u>

- 1. Housing: Silver plated
- 2. Pin: Gold plated
- 3. Coplanarity specification: 0.10 [.004] MAX.

## **Specifications**

Parameter	Minimum	Typical	Maximum				
Frequency Range (MHz)	1625		1680				
Insertion Loss: 1 to 2 (dB)		< .25	.30				
Isolation: 2 to 1(dB)	20	> 23					
Return Loss: 1, 2 (dB)	20	> 23					

## Notes:


- 1. Typical Values Represent Performance @ +23 °C.
- 2. Isolator Flange held to +85°C; 30 Min. maximum Duration.

## Power & Temperature Ratings

Parameter	Maximum
Forward PWR Peak/AVG	500/100 Watts
Reverse Power CW	20 Watts
Termination Rating (See Note 2)	20 Watts
Operating Temperature	-40 to +85° C
Storage Temperature	-50 to +125° C

Permanent damage to the Device or reduce reliability if exceeding any of the limits

Port (1) and (2): DC connected and floating with the 50 ohm resistance of the internal load as the only ground connection.



CW SMD ISOLATOR MODEL: RFSL5405

