




RoHS

	─ —19.0 [.75]—	-
2.3 [.09] TYP.	2X 14.5 [.57]	4X R1.5 [R.06]
<u> </u>	+	2X 6.2 [.24]
 2X 14.5 [.57]	1 RFCI 2 RFCR2849D	
<u> </u>	+ 3	3X TAB LEAD SEE NOTE 2
3X 1	.0 [.04]	4X Ø2.8 [Ø.11] THRU.

В


ADD ISOMETRIC VIEW



18-010

11/14/18

P.T



Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	2300		2500
Insertion Loss: In-Out (dB)		< .20	.30
Isolation: Out-In (dB)	22	> 25	
Return Loss (dB)	22	> 25	

Notes:

- 1. Typical Values Represent Performance @ +23 °C.
- 2. Tab Dimensions: 1.00 [.040]W x 2.5[.10]L x 0.25[.010]T
- 3. Body Flange held to+85°C Max.
- 4. S-Parameters to be measured by connecting Port 1 and 2 to VNA, and Port 3 to Load with return loss 30dB or higher

Terminal:

Port (1)-(2): Input-Output

Port (2)-(3) Port (3)-(1)

Power & Temperature Ratings

Parameter	Maximum	
Forward PWR Peak/AVG	1000/100 Watts	
Reverse Power CW (see note 3)	100 Watts	
Operating Temperature	-40 to +85° C	
Storage Temperature	-40 to +95° C	

Permanent damage to the Device or reduce reliability if exceeding any of the limits.

Port (1),(2)and (3): DC connected and floating as the only ground connection.

CW CIRCULATOR MODEL: RFCR2849D

