


THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY. DO NOT REVISE MANUALLY.



REVISIONS

REV.	DESCRIPTION	ECO	DATE	APPROVED
A	INITIAL RELEASE	I.R.	04/13/15	P.T



Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	1920		2125
Insertion Loss (dB)		< .25	.35
Isolation (dB)	20	> 23	
Return Loss (dB)	20	> 23	
FWD IMD: 2T at 37W per T 5MHz Spacing (dBc)		70	



Power & Temperature Ratings

Parameter	Maximum
Forward PWR Peak/AVG	1000/100 Watts
Reverse Power CW	20 Watts
Termination Rating (See Note 3)	20 Watts
Operating Temperature	-40 to +85° C
Storage Temperature	-40 to +95° C

Notes:

1. Typical Values Represent Performance @ +23 °C.
2. Tab Dimensions: 1.00 [.040]W x 3.0[.12]L x 0.20[.008]T
3. Isolator Flange held to +85°C; 30 Minute Maximum Duration

CW ISOLATOR MODEL: RFSL2637

<div>UNLESS OTHERWISE SPECIFIED</div> <div>ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]:</div> <div>TOLERANCES ARE:</div> <div><div>1 PLACE DECIMAL ±.2 [±.01]</div><div>2 PLACE DECIMAL ±.10 [±.004]</div><div>ANGULAR: ±1.0°</div><div>SURFACE ROUGHNESS 16/</div></div>			<div>THIRD ANGLE PROJECTION</div> <div></div>		<div>RFCI</div> <div></div>							
<div>REMOVE ALL BURRS AND BREAK SHARP EDGES.</div> <div>SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1</div> <div>DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5</div> <div>PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RF CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES.</div> <div>THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."</div>			<div>APPROVALS</div> <div>DATE</div>		<div>TITLE</div> <div>OUTLINE/SPECS</div>							
			DRAWN BY:		SIZE		CAGE NO.		DWG NO.		REV.	
			CHECKED BY:		A				SL2637-OS		A	
			DESIGN BY:		SCALE: FULL				SHEET 1 OF 1			
			ENGINEER BY:									
			MFG. ENGR.									
			Q.A.									
			PROG. MGMT/MKT									