









## **Specifications**

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	2900		3100
Insertion Loss (dB)		< .20	.30
Isolation (dB)	22	> 25	
Return Loss (dB)	22	> 25	

## Notes:

- 1. Typical Values Represent Performance @ +23 °C.
- 2. Tab Dimensions: 1.00 [.040]W x 2.5[.10]L x 0.20[.008]T
- 3. S-Parameters to be measured by connecting Port 1 and 2 to VNA, and Port 3 to Load with return loss 30dB or higher

## Power & Temperature Ratings

Parameter	Maximum		
Forward PWR Peak/AVG	1000/100 Watts		
Reverse Power CW	100 Watts		
Operating Temperature	-40 to +85° C		
Storage Temperature	-40 to +95° C		

CW CIRCULATOR MODEL: RFCR2857

● €	<del>]</del>	DI					
APPROVALS	DATE						
DRAWN BY:							
CHECKED BY:		TITLE					
DESIGN BY:							
ENGINEER BY:		1	OUTLINE/SI LOS				
MFG. ENGR.		SIZE CAGE NO DWG NO REV.				Incv	
Q.A.		SIZE	E CAGE NO.		057.00		
PROG. MGMT/MKT		A			2857-OS	A	
		SCALE:	FULL		SHEET 1 O	F 1	
	DRAWN BY: CHECKED BY: DESIGN BY: ENGINEER BY: MFG, ENGR. Q.A.	DRAWN BY: CHECKED BY: DESIGN BY: ENGINEER BY: MFG. ENGR. Q.A.	DRAWN BY: CHECKED BY: DESIGN BY: ENGINEER BY: MFG, ENGR. Q.A. PROG, MGMT/MKT  TITLE  SIZE A	DRAWN BY:  CHECKED BY:  DESIGN BY:  ENGINEER BY:  MFG. ENGR.  Q.A.  PROG. MGMT/MKT  DATE  TITLE  SIZE  CAGE NO.  A	DRAWN BY: CHECKED BY: DESIGN BY: ENGINEER BY: MFG. ENGR. Q.A. PROG. MGMT/MKT  TITLE  OUTLINE/ SIZE CAGE NO. DWG NO. CR2	DRAWN BY:  CHECKED BY:  DESIGN BY: ENGINEER BY:  MFG. ENGR.  Q.A. PROG. MGMT/MKT  DATE  OUTLINE/SPECS  DUTLINE/SPECS  CAGE NO.  CR2857-OS	